

ULTRACURE® 8 DATA SHEET

EST. 1978

The **Ultracure**® **8** is a high output UV LED curing lamp designed to quickly and completely cure UV adhesives and sealants. This curing light has built-in power regulation, over temperature protection and is liquid cooled to ensure consistent long term operation while outputting a maximum intensity UV light. The **Ultracure**® **8** includes a focused lens that concentrates the ultraviolet light to provide an extended curing range of 3x the standard distance of an Ultracure® 6 while maintaining the light intensity needed to produce a curing reaction. The **Ultracure**® **8** can be installed alone or in a series to produce a UV light bath for UV curing applications.

Product Part #: 107-033

Features:

- UV LED curing lamp
- · Built-in power regulation and overheat protection
- · Green / red system status indicator
- Liquid cooled

Specifications:

- Dimensions: 2.275" x 1.25" x 1.86"
- 2.5/w cm² maximum output @365nm
- 24 vdc @ 700mA


Mounting:

- The Ultracure® 8 has three mounting options:
 - 4 x M4 x 0.7 on electrical connector end
 - 2 x M4 x 0.7 on both sides of the device

Warranty:

Standard 1 year from purchase date





UV Curve / UV Output Curve:

The Ultracure® 8 has an optimal distance for curing properties. The diagram below shows UV intensity vs. distance curve:

ULTRA VIOLET ENERGY (U.V.E.) GRAPH REF. ONLY - U.V. ENERGY 2.8 W/cm² 2.5 W/cm² 3.5 W/


OUTPUT U.V.E. GRAPH	2.5 W/cm² U. NENERGY
DISTANCE	
	.31 [7.93] 38 [9.65]

DISTANCE	ENERGY W/om²
Oin [Omm]	1.5
.19in [4.77mm]	2.5
.25in [6.35mm]	2.8
.31 in [7.93mm]	2.5
.38in [9.65mm]	1.5



ULTRACURE® 8 DATA SHEET


EST. 1978



Top View:

Liquid Cooling System 2 x M5 x 0.8 Holes

Bottom View:



EDS_UC8:0121-1.0