

SAFETY DATA SHEET

Fusionbond 371B

SECTION 1: IDENTIFICATION

1.1. Product identifier

Trade name: Fusionbond 371B

Product no.: MS-371B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the Adhesive

substance or mixture: Restricted to professional users.

Uses advised against: None known.

1.3. Details of the supplier of the safety data sheet

Company and address: Hernon Manufacturing Inc

121 Tech Drive FL 32771 Sanford

USA

T: +1-407-322-4000 www.hernon.com

Contact person: Hernon SDS Coordinator

E-mail: customerservice@hernon.com

SDS date: 1/2/2025

SDS Version: 1.0

Date of previous version: 1/2/2025 (1.0)

1.4. Emergency telephone number

Contact the poison control at 1-800-222-1222 (24/7) or use the webpoisoncontrol

(triage.webpoisoncontrol.org) to get specific guidance for your case.

VelocityEHS:

+1-800-255-3924 (USA)

+1-813-248-0585 (International)

1-300-954-583 (Australia)

0-800-591-6042 (Brazil)

400-120-0751 (China)

000-800-100-4086 (India)

800-099-0731 (Mexico)

Contract #: (MIS0002665)

SECTION 2: HAZARD(S) IDENTIFICATION

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)



2.1. Classification of the substance or mixture

Flam. Lig. 2; H225, Highly flammable liquid and vapour.

Skin Irrit. 2; H315, Causes skin irritation.

Skin Sens. 1; H317, May cause an allergic skin reaction.

STOT SE 3; H335, May cause respiratory irritation.

2.2. Label elements

Hazard pictogram(s):

Signal word: Danger

Hazard statement(s): Highly flammable liquid and vapour. (H225)

Causes skin irritation. (H315)

May cause an allergic skin reaction. (H317) May cause respiratory irritation. (H335)

Precautionary statement(s):

General:

Prevention: Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. (P210)

Keep container tightly closed. (P233) Avoid breathing mist/vapour. (P261)

Wash hands and exposed skin thoroughly after handling.

(P264)

Contaminated work clothing should not be allowed out of

the workplace. (P272)

Wear eye protection/protective clothing. (P280)

Response: Call a POISON CENTER/doctor if you feel unwell. (P312)

If skin irritation or rash occurs: Get medical

advice/attention. (P333+P313)

Take off contaminated clothing and wash it before reuse.

(P362+P364)

In case of fire: Use water mist/carbon dioxide/alcohol-

resistant foam to extinguish. (P370+P378)

Store in a well-ventilated place. Keep container tightly

closed. (P403+P233)

Store in a well-ventilated place. Keep cool. (P403+P235)

Dispose of contents/container in accordance with local

regulation (P501)

Additional labelling: Not applicable.

2.3. Other hazards

Additional warnings: The material contains peroxide forming substances in

Group C. Group C includes solvents and other chemicals, where the formation of peroxides may initiate exothermic

polymerisation.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS



3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
methyl methacrylate	CAS No.: 80-62-6	60-100%	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	
3,5-diethyl-1,2-dihydro-1- phenyl-2-propylpyridine	CAS No.: 34562-31-7	1-5%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319	

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

General information:	If breathing is irregu	ılar, drowsiness, los	ss of consciousness

or cramps: Call 911 and give immediate treatment (first

aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an

unconscious person water or other drink.

Inhalation: Upon breathing difficulties or irritation of the respiratory

tract: Bring the person into fresh air and stay with him/her.

Skin contact: IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use

solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact: If in eyes: Flush eyes with water or saline water (20-30 °C)

for at least 5 minutes. Remove contact lenses. Seek

medical assistance and continue flushing during transport.

Ingestion: If the person is conscious, rinse the mouth with water and

stay with the person. Never give the person anything to

drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do

not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns: Rinse with water until pain stops then continue to rinse for

30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed Call a POISON CENTER/doctor if you feel unwell.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.





Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

The product should be tested for peroxide formation or discarded after 6 months.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

- 1. Material appears to be degraded and or contaminated.
- 2. Material appears to be discolored.
- 3. Deterioration or distortion of storage container.
- 4. Thermal shock (sunlight).
- 5. Age of material exceeds recommended storage time.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material: Always store in containers of the same material as the

original container.

Storage conditions: Dry, cool and well ventilated

Store in unopened containers at a temperature between 45°F and 75°F (7°C and 24°C) unless otherwise labeled.

Protect from moisture.



Protect from sunlight.

Remove Static Electricity. Ground Container and Equipment. Keep in an area equipped with sprinklers.

Incompatible materials: Acids

Bases Peroxides

Strong oxidizing agents Combustible materials

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

methyl methacrylate

Short term exposure limit (STEL) (ACGIH TLV) (ppm): 100 Long term exposure limit (OSHA Table Z-1) (mg/m³): 410 Long term exposure limit (OSHA Table Z-1) (ppm): 100 Long term exposure limit (ACGIH TLV) (ppm): 50

Part 1910 - Occupational Safety and Health Standards (29 CFR 1910.1000 TABLE Z-1 - Limits for Air Contaminants)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a

regular basis.

General recommendations: Smoking, drinking and consumption of food is not allowed

in the work area.

Exposure scenarios: There are no exposure scenarios implemented for this

product.

Exposure limits: Professional users are subjected to the legally set

maximum concentrations for occupational exposure. See

occupational hygiene limit values above.

Appropriate technical measures: The formation of vapours must be kept at a minimum and

below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and

emergency showers are clearly marked.

Apply standard precautions during use of the product.

Avoid inhalation of vapours.

Hygiene measures: Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental

exposure:

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally: Use only protective equipment with a recognized

certification mark, e.g. the UL mark.

Respiratory Equipment:



If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Skin protection:

Recommended	Type/Category	Standards	
-	Protective Clothing		R

Hand protection: Nitrile Rubber

Eye protection:

Туре	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state: Liquid

▼ *Color:* Off White , Off White , Beige

Odor: Sharp/pungent
Odor threshold (ppm): No data available
pH: No data available

Density (q/cm^3) : 0.97

Kinematic viscosity: No data available Particle characteristics: No data available

Phase changes

Melting point/freezing point (°F): No data available

Softening point/range (°F): Does not apply to liquids.

Boiling point (°F): >214
Boiling point (°C): >101

Vapor pressure: <29.2 mmHg (20 °C)
Relative vapor density: No data available
Decomposition temperature (°F): No data available

Data on fire and explosion hazards

Flash point (°F): >50 Flash point (°C): >10

Flammability (°F): The material is ignitable.

Auto-ignition temperature (°F): No data available



Explosion limits (% v/v): No data available

Solubility

Solubility in water: Slightly soluble n-octanol/water coefficient (LogKow): No data available Solubility in fat (q/L): No data available

9.2. Other information

Evaporation rate (n-butylacetate =

100):

No data available

Other physical and chemical

parameters:

No data available.

Oxidizing properties: No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Highly reactive and can auto-polymerize as a result of internal peroxide accumulation. The peroxides formed in these reactions are extremely shock- and heat-sensitive.

10.2. Chemical stability

Risk of peroxide formation starting an exothermic polymerization.

10.3. Possibility of hazardous reactions, including those associated with foreseeable emergencies

None known.

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure. Incompatible Materials

Mechanical influences (e.g. Shock, pressure, impact, friction). Fire, sparks or other ignition sources.

Extremes of temperature

Sunlight

Moisture

10.5. Incompatible materials

Acids

Bases

Peroxides

Strong oxidizing agents

Reducing agents

Combustible materials

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity



Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

methyl methacrylate has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No data available.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

Fusionbond 371B



This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)

methyl methacrylate is listed with EPA Hazardous Waste Number: U162

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
DOT	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1	III	No	Limited quantitie s: 5 L Tunnel restrictio n code: (D/E) See below for additiona l informati on.
IMDG	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1	III	No	Limited quantitie s: 5 L EmS: F-E S-D See below for additiona I informati on.
IATA	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3	III	No	See below for



14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)		Env**	Other informat ion:
		Classification code: F1			additiona l informati on.

^{*} Packing group

Additional information

This product is within scope of the regulations of transport of dangerous goods. DOT / See § 172.101 Hazardous Materials Table for any information on special provisions, requirements, or warnings in connection with transport. See § 172.602, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport. IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. U.S. Federal regulations

TSCA (the non-confidential portion): methyl methacrylate is listed

3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine is listed

Clean Air Act: methyl methacrylate is regulated as a hazardous air

pollutant (HAPS)

EPCRA Section 302: None of the components are listed EPCRA Section 304: None of the components are listed

EPCRA section 313: methyl methacrylate is listed

CERCLA: methyl methacrylate is regulated with a Reportable

Quantity (RQ) of: 1000 pounds

Hazardous chemical inventory

reporting:

This product is subject to Tier II reporting.

State regulations

California / Prop. 65: None of the components are listed

Massachusetts / Right To Know Act: methyl methacrylate is listed

New Jersey / Right To Know Act: methyl methacrylate / Substance number: 1277

methyl methacrylate is on the Special Health Hazard

^{**} Environmental hazards



Substance List

—

New York / Right To Know Act: methyl methacrylate is listed

methyl methacrylate is regulated with a Reportable

Quantity (RQ) of: 1000 pounds

methyl methacrylate is regulated with a Treshold

Reporting Quantity (TRQ) of: 0 pounds

_

Pennsylvania / Right To Know Act: methyl methacrylate is listed

methyl methacrylate is hazardous to the environment (E)

__

15.4. Restrictions for application

Restricted to professional users.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

15.5. Demands for specific education

No specific requirements.

15.6. Additional information

Not applicable.

15.7. Chemical safety assessment

No

15.8. Sources

OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H302, Harmful if swallowed.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H335, May cause respiratory irritation.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response Compensation and Liability Act

DOT = Department of Transportation

EINECS = European Inventory of Existing Commercial chemical Substances





EPCRA = Emergency Planning and Community Right-To-Know Act

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HCIS = Hazardous Chemical Information System

HNOC = Hazards Not Otherwise Classified

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

NFPA = National Fire Protection Association

NIOSH = National Institute for Occupational Safety and Health

OECD = Organisation for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

PBT = Persistent, Bioaccumulative and Toxic

RCRA = Resource Conservation and Recovery Act

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SARA = Superfund Amendments and Reauthorization Act

SCL = A specific concentration limit.

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by HCS (29 CFR 1910.1200).

The classification of the mixture in regard to physical hazards has been based on experimental data

The safety data sheet is validated by

SDS Coordinator

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en