

SAFETY DATA SHEET

Nuts N' Bolts 225

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: Nuts N' Bolts 225
Product no.: MS-225

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Adhesive
Restricted to professional users.
Uses advised against: None known.

1.3. Details of the supplier of the safety data sheet

Company and address: **Hernon Manufacturing Inc**
121 Tech Drive
FL 32771 Sanford
USA
T: +1-407-322-4000
www.hernon.com

Contact person: Hernon SDS Coordinator
E-mail: customerservice@hernon.com

Revision: 05/07/2024

SDS Version: 2.0

Date of previous version: 05/07/2024 (2.0)

1.4. Emergency telephone number

Contact the poison control at 1-800-222-1222 (24/7) or use the webpoisoncontrol (triage.webpoisoncontrol.org) to get specific guidance for your case.

VelocityEHS:

+1-800-255-3924 (USA)

+1-813-248-0585 (International)

1-300-954-583 (Australia)

0-800-591-6042 (Brazil)

400-120-0751 (China)

000-800-100-4086 (India)

800-099-0731 (Mexico)

Contract #: (MIS0002665)

SECTION 2: HAZARDS IDENTIFICATION

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.
Skin Sens. 1; H317, May cause an allergic skin reaction.
Eye Irrit. 2; H319, Causes serious eye irritation.
STOT SE 3; H335, May cause respiratory irritation.
Carc. 1B; H350, May cause cancer.
Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

Causes skin irritation. (H315)
May cause an allergic skin reaction. (H317)
Causes serious eye irritation. (H319)
May cause respiratory irritation. (H335)
May cause cancer. (H350)
Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s):

General:

-

Prevention:

Obtain special instructions before use. (P201)
Wear eye protection/protective clothing. (P280)

Response:

IF exposed or concerned: Get medical advice/attention.
(P308+P313)
If skin irritation or rash occurs: Get medical
advice/attention. (P333+P313)

Storage:

Store in a well-ventilated place. Keep container tightly
closed. (P403+P233)

Disposal:

Dispose of contents/container in accordance with local
regulation
(P501)

Hazardous substances:

Polyethylene Glycol Dimethacrylate
Hydroxypropyl Methacrylate
Cumene hydroperoxide
N,N-dimethyl-m-toluidine
Cumene

Additional labelling:

Restricted to professional users.

2.3. Other hazards

Additional warnings:

This mixture/product does not contain any substances
known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered
to be endocrine disruptors in accordance with the criteria
set out in Commission Delegated Regulation (EU)
2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Polyethylene Glycol Dimethacrylate	CAS No.: 25852-47-5 EC No.: 607-819-8 UK-REACH: Index No.:	40-70%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 3, H412	
Hydroxypropyl Methacrylate	CAS No.: 27813-02-1 EC No.: 248-666-3 UK-REACH: Index No.:	1-5%	Skin Sens. 1, H317 Eye Irrit. 2, H319	
Cumene hydroperoxide	CAS No.: 80-15-9 EC No.: 201-254-7 UK-REACH: Index No.: 617-002-00-8	1-5%	Org. Perox. E, H242 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 (SCL: 10.00 %) Skin Irrit. 2, H315 (SCL: 3.00 %) Eye Dam. 1, H318 Acute Tox. 3, H331 STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 1, H410 (M=1)	
N,N-dimethyl-m-toluidine	CAS No.: 99-97-8 EC No.: 202-805-4 UK-REACH: Index No.: 612-056-00-9	0.1-1%	Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Sens. 1, H317 Acute Tox. 2, H330 Carc. 1B, H350 Repr. 2, H361 STOT RE 2, H373 Aquatic Chronic 3, H412	
Cumene	CAS No.: 98-82-8 EC No.: 202-704-5 UK-REACH: Index No.: 601-024-00-X	0.1-1%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 Carc. 1B, H350 Aquatic Chronic 3, H412	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

<i>General information:</i>	In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.
<i>Inhalation:</i>	Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.
<i>Skin contact:</i>	Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.
<i>Eye contact:</i>	If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.
<i>Ingestion:</i>	If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.
<i>Burns:</i>	Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Sulphur oxides

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Store locked up. A sign warning of toxic materials shall be affixed the room and cupboard

containing the product(s).

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material: Always store in containers of the same material as the original container.

Storage conditions: Keep at temperatures between 7 and 29 °C.

Incompatible materials: Reducing agents
Strong oxidizing agents

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Cumene

Long term exposure limit (8 hours) (ppm): 25

Long term exposure limit (8 hours) (mg/m³): 125

Short term exposure limit (15 minutes) (ppm): 50

Short term exposure limit (15 minutes) (mg/m³): 250

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.

EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

Cumene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	1.2 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	15.4 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	16.6 mg/m ³
Long term – Systemic effects - Workers	Inhalation	100 mg/m ³
Short term – Local effects - Workers	Inhalation	250 mg/m ³
Long term – Systemic effects - General population	Oral	5 mg/kg bw/day

Cumene hydroperoxide

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Inhalation	6 mg/m ³

Hydroxypropyl Methacrylate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	2.5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	4.2 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	4.35 mg/m ³

Long term – Systemic effects - Workers	Inhalation	14.7 mg/m ³
Long term – Systemic effects - General population	Oral	2.5 mg/kg bw/day

N,N-dimethyl-m-toluidine

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	223 µg/kgbw/day
Long term – Systemic effects - Workers	Dermal	624 µg/kgbw/day
Long term – Systemic effects - General population	Inhalation	22.7 µg/m ³
Long term – Systemic effects - Workers	Inhalation	128 µg/m ³
Long term – Systemic effects - General population	Oral	20 µg/kgbw/day

PNEC

Cumene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		35 µg/L
Freshwater sediment		3.22 mg/kg
Intermittent release (freshwater)		12 µg/L
Marine water		3.5 µg/L
Marine water sediment		322 µg/kg
Sewage treatment plant		200 mg/L
Soil		624 µg/kg

Cumene hydroperoxide

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3.1 µg/L
Freshwater sediment		23 µg/kg
Intermittent release (freshwater)		31 µg/L
Marine water		310 ng/L
Marine water sediment		2.3 µg/kg
Sewage treatment plant		350 µg/L
Soil		2.9 µg/kg

Hydroxypropyl Methacrylate

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		904 µg/L
Freshwater sediment		6.28 mg/kg
Intermittent release (freshwater)		972 µg/L
Marine water		90.4 µg/L
Marine water sediment		6.28 mg/kg
Sewage treatment plant		10 mg/L
Soil		727 µg/kg

N,N-dimethyl-m-toluidine

Route of exposure:	Duration of Exposure:	PNEC:
--------------------	-----------------------	-------

Freshwater		152.59 µg/L
Freshwater sediment		45.378 mg/kg
Intermittent release (freshwater)		152.59 µg/L
Marine water		15.259 µg/L
Marine water sediment		45.378 mg/kg
Sewage treatment plant		4.286 mg/L
Soil		18.677 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations: Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios: There are no exposure scenarios implemented for this product.

Exposure limits: Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures: Do not recirculate outlet air that contain the substances. The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures: Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure: Keep damming materials near the workplace. If possible, collect spillage during work.


Individual protection measures, such as personal protective equipment

Generally: Use only UKCA marked protective equipment.

Respiratory Equipment:

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.


Skin protection:

Recommended	Type/Category	Standards	
-	Protective Clothing		

Hand protection:

Nitrile Rubber

Eye protection:

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Colour:</i>	Red
<i>Odour / Odour threshold:</i>	Mild
<i>pH:</i>	Testing not relevant or not possible due to the nature of the product.
<i>Density (g/cm³):</i>	1.08
<i>Kinematic viscosity:</i>	Testing not relevant or not possible due to the nature of the product.
<i>Particle characteristics:</i>	Does not apply to liquids.

Phase changes

<i>Melting point/Freezing point (°C):</i>	Testing not relevant or not possible due to the nature of the product.
<i>Softening point/range (°C):</i>	Does not apply to liquids.
▼ <i>Boiling point (°C):</i>	>149.0
▼ <i>Vapour pressure:</i>	<5.0 mmHg (26.6 °C)
<i>Relative vapour density:</i>	Testing not relevant or not possible due to the nature of the product.
<i>Decomposition temperature (°C):</i>	Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

▼ <i>Flash point (°C):</i>	>93.3
<i>Flammability (°C):</i>	Testing not relevant or not possible due to the nature of the product.
<i>Auto-ignition temperature (°C):</i>	Testing not relevant or not possible due to the nature of the product.
<i>Lower and upper explosion limit (% v/v):</i>	Testing not relevant or not possible due to the nature of the product.

Solubility

<i>Solubility in water:</i>	Testing not relevant or not possible due to the nature of the product.
<i>n-octanol/water coefficient (LogKow):</i>	Testing not relevant or not possible due to the nature of the product.
<i>Solubility in fat (g/L):</i>	Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Other physical and chemical parameters:

No data available.

Oxidizing properties:

Testing not relevant or not possible due to the nature of the product.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Incompatible Materials

10.5. Incompatible materials

Reducing agents

Strong oxidizing agents

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Carcinogenic effects: This product contains substances considered or proven to be carcinogenic. The carcinogenic effects may be triggered subsequent to exposure through inhalation, skin contact or ingestion.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

N,N-dimethyl-m-toluidine has been classified by IARC as a group 2B carcinogen.

Cumene has been classified by IARC as a group 2B carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
 HP 7 – Carcinogenic
 HP 13 – Sensitising
 HP 14 – Ecotoxic
 Dispose of contents/container to an approved waste disposal plant.
 Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
 EWC code: Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application:

Restricted to professional users.
 People under the age of 18 shall not be exposed to this product.
 Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education:

No specific requirements.

SEVESO - Categories / dangerous substances:

Not applicable.

REACH, Annex XVII:

Cumene is subject to UK-REACH restrictions (entry 40).

Additional information:

Not applicable.

Sources:

The Management of Health and Safety at Work

Regulations 1999.
The Health and Safety at Work etc. Act 1974 Regulations 2013.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.
H242, Heating may cause a fire.
H301, Toxic if swallowed.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H311, Toxic in contact with skin.
H312, Harmful in contact with skin.
H314, Causes severe skin burns and eye damage.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H330, Fatal if inhaled.
H331, Toxic if inhaled.
H335, May cause respiratory irritation.
H336, May cause drowsiness or dizziness.
H350, May cause cancer.
H361, Suspected of damaging fertility or the unborn child.
H373, May cause damage to organs through prolonged or repeated exposure.
H410, Very toxic to aquatic life with long lasting effects.
H412, Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The safety data sheet is validated by

SDS Coordinator

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en