

SURESHOT® 3000 DATA SHEET

EST. 1978

The **Sureshot® 3000** is a precise, digital volumetric dispensing valve for a wide range of low and medium viscosity fluids. With multiple models to choose from, the **Sureshot® 3000** utilizes a chemically inert ceramic piston which ensures long-term, drift free fluid control. The **Sureshot® 3000** is Hernon's most accurate volume dispensing valve and is ideal for dispensing ultraviolet formulas, epoxies, methacrylate's, anaerobics, cyanoacrylates, fluxes and more. For precise production applications, this valve can be relied upon to support extended manufacturing runs without variation or breakdowns.

Standard Assembled Model Part #'s:

- 110-061 Aluminum pump body piston 0.250
- 110-062 Aluminum pump body piston 0.375
- 110-063 Stainless steel pump body piston 0.25
- 110-064 Stainless steel pump body piston 0.375

Features:

- · Compact design, easy mounting
- Precision volumetric dispensing
- · Quick and easy maintenance
- · Diverse chemical compatibility
- · Robust construction

Specifications:

- Available in ¼" and ¾" piston sizes
- Length: 2.462" (62.53 mm)
 Width: 2.0" (50.8 mm)
 Height: 1.75" (44.45 mm)
- Weight: 657.7 grams (23.2 oz) stainless steel body
 Weight: 328.9 grams (11.6 oz) aluminum body


Dispense Tips:

Tip selection is critical to achieve optimum valve performance. SS3000 series valves offer the option of a Luer-lock adapter and one dispensing tip kit for the fluid control. The kit (PT# 110-033) includes smooth-flow tapered micro-tips in sizes from 14 to 25 gauge, and precision stainless steel tips in sizes from 14 to 30 gauge.

Warranty:

· Standard 1 year from purchase date









SURESHOT® 3000 DATA SHEET

EST. 1978





EDS-2200_3.0