

SAFETY DATA SHEET

Self Sealer 616

SECTION 1: IDENTIFICATION

1.1. Product identifier

Trade name: Self Sealer 616

Product no.: MS-616

1.2. Relevant identified uses of the substance or mixture and uses advised against

▼ Relevant identified uses of the Sealant

substance or mixture: Restricted to professional users.

Uses advised against: None known.

1.3. Details of the supplier of the safety data sheet

Company and address: Hernon Manufacturing Inc

121 Tech Drive FL 32771 Sanford

USA

T: +1-407-322-4000 www.hernon.com

Contact person: Hernon SDS Coordinator

E-mail: customerservice@hernon.com

SDS date: 2/16/2025

SDS Version: 1.0

Date of previous version: 2/16/2025 (1.0)

1.4. Emergency telephone number

Contact the poison control at 1-800-222-1222 (24/7) or use the webpoisoncontrol (triage.webpoisoncontrol.org) to get specific guidance for your case.

VelocityEHS:

+1-800-255-3924 (USA)

+1-813-248-0585 (International)

1-300-954-583 (Australia)

0-800-591-6042 (Brazil)

400-120-0751 (China)

000-800-100-4086 (India)

800-099-0731 (Mexico)

Contract #: (MIS0002665)

SECTION 2: HAZARD(S) IDENTIFICATION

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)



2.1. Classification of the substance or mixture

Skin Sens. 1; H317, May cause an allergic skin reaction.

Repr. 2; H361, Suspected of damaging fertility or the unborn child.

2.2. Label elements

Hazard pictogram(s):

!

Signal word: Warning

Hazard statement(s): May cause an allergic skin reaction. (H317)

Suspected of damaging fertility or the unborn child. (H361)

Precautionary statement(s):

General: -

Prevention: Obtain special instructions before use. (P201)

Avoid breathing mist/vapour. (P261)

Contaminated work clothing should not be allowed out of

the workplace. (P272)

Wear eye protection/protective clothing. (P280)

Response: IF exposed or concerned: Get medical advice/attention.

(P308+P313)

If skin irritation or rash occurs: Get medical

advice/attention. (P333+P313)

Take off contaminated clothing and wash it before reuse.

(P362+P364)

Storage: -

Disposal: Dispose of contents/container in accordance with local

regulation (P501)

Additional labelling: Not applicable.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Mica	CAS No.: 12001-26-2	10-30%		
Titanium dioxide	CAS No.: 13463-67-7	10-30%		
Polyethylene Homopolymer	CAS No.: 9002-88-4	1-5%		
Ethylene Glycol Monobutyl Ether	CAS No.: 111-76-2	3-7%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319	



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

			Acute Tox. 3, H331	
Polytetrafluoroethylene	CAS No.: 9002-84-0	1-5%		
ammonia	CAS No.: 1336-21-6 <1% Skin Corr. 1B, H314 STOT SE 3, H335 (SCL: 5.00 %)			

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

General information: If breathing is irregular, drowsiness, loss of consciousness

or cramps: Call 911 and give immediate treatment (first

aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an

unconscious person water or other drink.

Inhalation: Upon breathing difficulties or irritation of the respiratory

tract: Bring the person into fresh air and stay with him/her.

Skin contact: Remove contaminated clothing and shoes immediately.

Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or

thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact: If in eyes: Flush eyes with water or saline water (20-30 °C)

for at least 5 minutes. Remove contact lenses. Seek

medical assistance and continue flushing during transport.

Ingestion: If the person is conscious, rinse the mouth with water and

stay with the person. Never give the person anything to

drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid

inhalation of or choking on vomited material.

Burns: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters. If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste. See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.





See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent

leakage.

Recommended storage material: Always store in containers of the same material as the

original container.

Storage conditions: Keep at temperatures between 7 and 29 °C.

Do Not Freeze

Dry, cool and well ventilated

Incompatible materials: Acids

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Titanium dioxide

Long term exposure limit (ACGIH TLV) (mg/m³): 10

Long term exposure limit (NIOSH REL) (mg/m³): Potential occupational carcinogen; (ultrafine particles) / 2.4 (fine) / 0.3 (ultrafine)

Ethylene Glycol Monobutyl Ether

Long term exposure limit (OSHA Table Z-1) (mg/m³): 240 Long term exposure limit (OSHA Table Z-1) (ppm): 50 Long term exposure limit (ACGIH TLV) (ppm): 20

Part 1910 - Occupational Safety and Health Standards (29 CFR 1910.1000 TABLE Z-1 - Limits for Air Contaminants)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations: Smoking, drinking and consumption of food is not allowed

in the work area.

Exposure scenarios: There are no exposure scenarios implemented for this

product.

Exposure limits: Professional users are subjected to the legally set

maximum concentrations for occupational exposure. See

occupational hygiene limit values above.

Appropriate technical measures: The formation of vapours must be kept at a minimum and

below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and

emergency showers are clearly marked.

Apply standard precautions during use of the product.

Avoid inhalation of vapours.

Hygiene measures: In between use of the product and at the end of the

working day all exposed areas of the body must be washed



thoroughly. Pay special attention to hands, forearms and

face.

Measures to avoid environmental

exposure:

Keep damming materials near the workplace. If possible,

collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally: Use only protective equipment with a recognized

certification mark, e.g. the UL mark.

Respiratory Equipment:

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Skin protection:

Recommended	Type/Category	Standards	
-	Protective Clothing		R

Hand protection: Nitrile Rubber

Eye protection:

Туре	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state: Liquid Color: White

Odor: Ammonia odor
Odor threshold (ppm): No data available

pH: 8 - 10 *Density (g/cm³)*: 1.24

Relative density: No data available Kinematic viscosity: No data available Particle characteristics: No data available

Phase changes

Melting point/freezing point (°F): No data available

Softening point/range (°F): Does not apply to liquids.

Boiling point (°F): >212 Boiling point (°C): >100



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

Vapor pressure: <20.0 mmHg (20 °C)

Relative vapor density: <1

Decomposition temperature (°F): No data available

Data on fire and explosion hazards

Flash point (°F): >200 Flash point (°C): >94

Flammability (°F):

Auto-ignition temperature (°F):

Explosion limits (% v/v):

No data available

No data available

Solubility

Solubility in water:

n-octanol/water coefficient (LogKow):

No data available

Solubility in fat (q/L):

No data available

9.2. Other information

Evaporation rate (n-butylacetate =

100):

No data available

Other physical and chemical

parameters:

No data available.

Oxidizing properties: No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions, including those associated with foreseeable emergencies

None known.

10.4. Conditions to avoid

Incompatible Materials Extremes of temperature Frost

10.5. Incompatible materials

Acids

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects



Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

None known.

Other information

Titanium dioxide has been classified by IARC as a group 2B carcinogen.

Polyethylene Homopolymer has been classified by IARC as a group 3 carcinogen.

Ethylene Glycol Monobutyl Ether has been classified by IARC as a group 3 carcinogen.

Polytetrafluoroethylene has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No data available.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects



None known.

SECTION 13: DISPOSAL CONSIDERATIONS

RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)

None of the components are listed

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

		14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	Env**	Other informat ion:
DOT	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

^{*} Packing group

Self Sealer 616

Additional information

Not dangerous goods according to DOT, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. U.S. Federal regulations

TSCA (the non-confidential portion): Titanium dioxide is listed

Polyethylene Homopolymer is listed Ethylene Glycol Monobutyl Ether is listed

Polytetrafluoroethylene is listed

ammonia is listed

Clean Air Act:

None of the components are listed

EPCRA Section 302:

None of the components are listed

EPCRA Section 304:

None of the components are listed

EPCRA section 313: ammonia is listed

CERCLA: ammonia is regulated with a Reportable Quantity (RQ) of:

www.almego.com

^{**} Environmental hazards





1000 pounds

Hazardous chemical inventory

reporting:

This product is subject to Tier II reporting.

State regulations

California / Prop. 65: None of the components are listed

Massachusetts / Right To Know Act: Mica is listed

Titanium dioxide is listed

Ethylene Glycol Monobutyl Ether is listed

ammonia is listed

New Jersey / Right To Know Act: Mica / Substance number: 1659

Titanium dioxide / Substance number: 1861

Ethylene Glycol Monobutyl Ether / Substance number:

0275

Ethylene Glycol Monobutyl Ether is on the Special Health

Hazard Substance List

ammonia / Substance number: 0103

ammonia is on the Special Health Hazard Substance List

_

New York / Right To Know Act: Titanium dioxide is listed

Titanium dioxide is regulated with a Treshold Reporting

Quantity (TRQ) of: 100 pounds

Ethylene Glycol Monobutyl Ether is listed

Ethylene Glycol Monobutyl Ether is regulated with a Treshold Reporting Quantity (TRQ) of: 10 pounds

_

ammonia is listed

ammonia is regulated with a Reportable Quantity (RQ) of:

1000 pounds

ammonia is regulated with a Treshold Reporting Quantity

(TRQ) of: 100 pounds

—

Pennsylvania / Right To Know Act: Mica is listed

Titanium dioxide is listed

Ethylene Glycol Monobutyl Ether is listed

Polytetrafluoroethylene is listed

_

ammonia is listed

ammonia is hazardous to the environment (E)

15.4. Restrictions for application

Restricted to professional users.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must



be considered.

15.5. Demands for specific education

No specific requirements.

15.6. Additional information

Not applicable.

15.7. Chemical safety assessment

Nο

15.8. Sources

OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H302, Harmful if swallowed.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H319, Causes serious eye irritation.

H331, Toxic if inhaled.

H335, May cause respiratory irritation.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response Compensation and Liability Act

DOT = Department of Transportation

EINECS = European Inventory of Existing Commercial chemical Substances

EPCRA = Emergency Planning and Community Right-To-Know Act

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HCIS = Hazardous Chemical Information System

HNOC = Hazards Not Otherwise Classified

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

NFPA = National Fire Protection Association

NIOSH = National Institute for Occupational Safety and Health

OECD = Organisation for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

PBT = Persistent, Bioaccumulative and Toxic

RCRA = Resource Conservation and Recovery Act





RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SARA = Superfund Amendments and Reauthorization Act

SCL = A specific concentration limit.

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by HCS (29 CFR 1910.1200).

The safety data sheet is validated by

SDS Coordinator

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en