

SAFETY DATA SHEET

Issue Date 30-Mar-2015 Revision Date 24-Feb-2021 Version 1

1. IDENTIFICATION

Product identifier

Product Name Ultrabond 736

Other means of identification

Product Code MS-736 UN/ID no. None Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use UV Coating. Uses advised against None known

Details of the supplier of the safety data sheet

Manufacturer Address
Hernon Manufacturing Inc.
121 Tech Drive
Sanford, FL 32771
800-527-0004

Emergency telephone number

Company Phone Number 407-322-4000

Emergency Telephone Chemtel 800-255-3924

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 4

Label elements

Emergency Overview

Warning

Hazard statements

Harmful if swallowed

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause respiratory irritation. May cause drowsiness or dizziness.

Combustible liquid

MS-736 - Ultrabond 736 Revision Date 24-Feb-2021



Appearance No information available

Physical state Liquid

Odor Mild

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Contaminated work clothing must not be allowed out of the workplace

Keep away from flames and hot surfaces. - No smoking

Wear protective gloves/eye protection/face protection

Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of water and soap

Take off contaminated clothing and wash it before reuse

If skin irritation or rash occurs: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell

Rinse mouth

In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful in contact with skin.

Very toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
URETHANE METHACRYLATE	Proprietary	40 - 70	*
HYDROXYETHYL METHACRYLATE	868-77-9	7 - 13	*
ISOBORNYL METHACRYLATE	7534-94-3	5 - 10	*
T-BUTYL PERBENZOATE	614-45-9	1 - 5	*
ACRYLIC ACID	79-10-7	1 - 5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

MS-736 - Ultrabond 736 Revision Date 24-Feb-2021

Eye contactRinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact Wash with soap and water. Flush skin with water for several minutes. Remove

contaminated clothing and shoes. If irritation develops, seek medical attention. Wash

clothing before reuse.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give

artificial respiration. Get medical attention immediately.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use CO2, dry chemical, or foam.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

No information available.

Hazardous combustion products Carbon oxides. Nitrogen oxides (NOx). Irritating organic vapors.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

confined areas.

Environmental precautions

Environmental precautions Do not allow into any sewer, on the ground or into any body of water. Collect spillage. See

Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

MS-736 - Ultrabond 736 Revision Date 24-Feb-2021

Methods for cleaning up Soak up with inert absorbent material. Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Wash thoroughly

after handling. Ensure adequate ventilation, especially in confined areas.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep at temperatures between 8 and 28 °C.

Incompatible materials Strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACRYLIC ACID	TWA: 2 ppm	(vacated) TWA: 10 ppm	TWA: 2 ppm
79-10-7	S*	(vacated) TWA: 30 mg/m ³	TWA: 6 mg/m ³
		(vacated) S*	_

Appropriate engineering controls

Engineering Controls Showers

> Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing. Use rubber or plastic gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

> respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance No information available Odor Mild

Color Light amber **Odor threshold** No information available

Property Values Remarks • Method

Does not apply

Melting point / freezing point

No information available Boiling point / boiling range 149 °C / 300 °F

77 °C / 171 °F Flash point **Evaporation rate** No information available Flammability (solid, gas) No information available

MS-736 - Ultrabond 736 Revision Date 24-Feb-2021

Flammability Limit in Air

Upper flammability limit:8.0% Acrylic AcidLower flammability limit:2.0% Acrylic AcidVapor pressureNo information availableVapor densityNo information available

Relative density 1.10
Water solubility Low

Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other Information

Softening point
Molecular weight
VOC Content (%)
Density
No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Incompatible materials.

Incompatible materials

Strong oxidizers.

Hazardous Decomposition Products

Carbon oxides. Nitrogen oxides (NOx). Irritating organic vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

InhalationNo data availableEye contactNo data availableSkin contactNo data availableIngestionNo data available

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
HYDROXYETHYL METHACRYLATE 868-77-9	= 5050 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
T-BUTYL PERBENZOATE	= 1012 mg/kg (Rat)	-	-

Revision Date 24-Feb-2021

614-45-9						
ACRYLIC ACID	= 193 mg/kg	(Rat) = $33500 \mu g/kg$	= 280 µL/kg	(Rabbit) = 295 mg/kg	= 11.1 mg/L (Rat) 1 h = 3.6 mg/L
79-10-7		(Rat)		(Rabbit)	(R	at) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicityNo information available.
No information available.

Carcinogenicity

Chemical Name	ACGIH	IARC	NTP	OSHA
ACRYLIC ACID	-	Group 3	-	-
79-10-7				

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard

No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document.

 ATEmix (oral)
 1,730.40 mg/kg

 ATEmix (dermal)
 2,360.80 mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
HYDROXYETHYL	-	213 - 242: 96 h Pimephales	=
METHACRYLATE		promelas mg/L LC50 flow-through	
868-77-9		227: 96 h Pimephales promelas	
		mg/L LC50	
ACRYLIC ACID	0.17: 96 h Pseudokirchneriella	222: 96 h Brachydanio rerio mg/L	95: 48 h Daphnia magna mg/L
79-10-7	subcapitata mg/L EC50 0.04: 72 h	LC50 semi-static	EC50 270: 24 h Daphnia magna
	Desmodesmus subspicatus mg/L		mg/L LC50 Static
	FC50		-

Persistence and degradability

No information available.

Bioaccumulation

Bioaccamalation	
Chemical Name	Partition coefficient
HYDROXYETHYL METHACRYLATE 868-77-9	0.47
ACRYLIC ACID 79-10-7	0.38 - 0.46

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

MS-736 - Ultrabond 736 Revision Date 24-Feb-2021

Contaminated packaging Do not reuse container.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
ACRYLIC ACID	-	-	-	U008
79-10-7				

Chemical Name	California Hazardous Waste Status
T-BUTYL PERBENZOATE	Ignitable
614-45-9	Reactive

14. TRANSPORT INFORMATION

DOT Not regulated

UN/ID no. None

Proper shipping name Not regulated **Hazard Class**

None **Packing Group** None **Special Provisions** None

IATA Not regulated

UN/ID no. None

Proper shipping name Not regulated

Hazard Class None **Packing Group** None **Special Provisions** None

IMDG Not regulated

UN/ID no. None

Proper shipping name Not regulated

Hazard Class None **Packing Group** None **Special Provisions** None

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies Complies **ENCS IECSC** Complies **KECL** Complies Complies **PICCS** Complies **AICS**

All ingredients are on the inventory or are exempt from listing.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical

MS-736 - Ultrabond 736

Revision Date 24-Feb-2021

or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
ACRYLIC ACID - 79-10-7	1.0

SARA 311/312 Hazard Categories

Acute health hazard Chronic Health Hazard Fire hazard Sudden release of pressure hazard Reactive Hazard -

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACRYLIC ACID	5000 lb	-	RQ 5000 lb final RQ
79-10-7			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
T-BUTYL PERBENZOATE	X	X	X
614-45-9			
ACRYLIC ACID	X	X	X
79-10-7			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION. INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards - Flammability - Instability - Physical and Chemical

Properties -

<u>HMIS</u> Health hazards - Flammability - Physical hazards - Personal protection -

Prepared By SDS coordinator Issue Date 30-Jun-2015 Revision Date 24-Feb-2021

Revision Note No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet